

360° Combi Crushers

CK Series

For carriers from 7,7 to 55 tons



360° Combi Crushers CK Series

Rotating 360° Crusher for primary, secondary and selected demolition with FAST JAWS CHANGE SYSTEM.

With 5 available jaws the change system is fully hydraulic and semi-automatic to guarantee versatility and safety, without losing power and speed.

The CK attachment allows you to do every kind of demolition:

- Primary Demolition: to separate or reduce in smaller scraps what has been already demolished
- Secondary Demolition: where it will be necessary to extract and recuperate elements or precious components (copper, aluminum, iron, steel, wood...) or for the drainage of area of environmental impact in which the presence of toxic, inflammable and contaminating materials.

360° Combi Crushers - CK Series

Models		CK07	CK14	CK21	CK28	CK36
Rotation	°	360	360	360	360	360
Rotation Flow	gal/min	1 / 2	5 / 7	5 / 7	5 / 7	10 / 13
Rotation Pressure	psi	1714	1714	1714	1714	1714
Open / Close Flow	gal/min	18 / 23	29 / 42	44 / 55	52 / 65	79 / 105
Open / Close pressure	psi	3285 / 5000	5000	5000	5000	5000
Weight	lbs	1078	2011	2720	3456	4644
Excavator Weight	1000 lbs	15 / 28	28 / 46	40 / 60	57 / 77	77 / 111


For dimensions and specifications, see the back of this page




360° Combi Crushers - CK Series

Specifications and Dimensions


"P" PULVERIZER JAWS



"D" DEMOLITION JAWS



"CH" JAWS




Models		CK07	CK14	CK21	CK28	CK36
A	in	63,78	78,54	82,20	93,62	101,77
B	in	21,06	28,35	30,71	35,04	38,58
C	in	20,67	28,74	30,71	34,65	36,61
D	in	6,69	10,24	10,24	11,81	13,39
E	in	11,42	14,96	14,96	16,54	18,50
Blade Length	in	3,35	5,91	7,87	7,87	7,87
F3	t	35	71	88	115	132
Total Weight	lbs	1702	3444	4691	6100	8356
Weight	lbs	624	1433	1971	2644	3711
	in	0,79	1,18	1,38	1,57	1,97


Models		CK07	CK14	CK21	CK28	CK36
A	in	62,80	78,50	81,65	92,76	100,59
B	in	20,47	28,23	30,71	34,06	37,68
C	in	19,69	27,56	29,92	31,89	35,83
D	in	1,97	2,76	2,76	3,15	3,54
E	in	7,48	9,45	9,45	10,63	11,81
Blade Length	in	3,35	5,91	7,87	7,87	7,87
F3	t	35	71	88	115	132
Total Weight	lbs	1578	3342	4591	5889	8033
Weight	lbs	500	1331	1871	2433	3389
	in	0,79	1,18	1,38	1,57	1,97

lbs		CK07	CK14	CK21	CK28	CK36
A	in	62,01	76,93	81,22	93,11	101,97
B / B1	in	14	24/16	29/21	33/27	36/30
C/C1	in	17	24/16	26/18	31/23	34/24
D/D1	in	8	2/8	2/10	3/11	3/12
E	in	11,81	13,78	15,35	17,32	19,29
F3	t	43	77	93	121	132
Total Weight	lbs	1716	3558	4844	6360	8689
Weight	lbs	638	1547	2124	2904	4044
	in	0,79	1,18	1,38	1,57	1,97

"S" STEEL JAWS



"R" COMBI JAWS



Models		CK07	CK14	CK21	CK28	CK36
A	in	58,07	71,89	72,95	84,02	92,52
B	in	10,43	15,43	15,43	19,29	21,85
C	in	13,19	19,41	19,41	23,62	22,05
D	in	3,54	4,13	4,13	4,72	4,72
E	in	10,24	11,02	11,81	14,96	16,34
F3	t	49	99	126	154	176
Total Weight	lbs	1622	3338	4504	5867	8022
Weight	lbs	544	1327	1784	2411	3378
	in	1,18	1,57	1,97	2,36	2,76
	in	0,24	0,39	0,47	0,59	0,79
	in	4,72	7,09	10,63	12,99	14,17
	in	/	5,51	7,87	9,45	10,24

lbs		CK07	CK14	CK21	CK28	CK36
A	in	62,80	78,50	81,50	96,85	100,59
B / B1	in	20/10	28/13	30/14	33/17	37/18
C/C1	in	18/11	27/13	29/13	31/16	35/19
D	in	2,36	2,76	2,76	3,54	4,33
E	in	9,06	10,24	10,24	13,39	14,96
Blade Length	in	11,02	13,39	13,39	16,93	19,29
F3	t	35	71,43	87,91	115,38	131,87
Total Weight	lbs	1704	3489	4696	6160	8378
Weight	lbs	627	1478	1976	2704	3778
	in	0,98	1,18	1,38	1,57	1,97
	in	3,94	6,30	9,45	10,63	12,99
	in	/	4,72	7,09	7,87	9,45