

Crushing Buckets

FB Series

For carriers from 13 to 61 tons



Crushing Buckets FB Series

- 5 models for carriers from 13 to 61t
- Adjustable size setting of Crushed material from 0,71 to 5 in
- Eccentric-moving jaws system
- Interchangeable anti-wear plow bolt inner plates
- Interchangeable crushing jaw kit
- Powerful Piston Motor
- Centralized greasing system



Crushing Buckets - FB Series



Crushing Buckets - FB Series

Specifications and Dimensions




INTERCHANGEABLE
IRON SEPARATOR KIT



INTERCHANGEABLE
CRUSHING JAWS KIT



INTERCHANGEABLE
INTERNAL WEAR
PLATES



Model		FB150 HD	FB250 HD	FB300 HD	FB350 HD	FB500 HD
A	in	29,13	35,43	40,55	44,49	55,91
B	in	70,87	80,71	80,71	84,65	88,58
C	in	43,31	52,36	52,36	55,12	57,09
D	in	23,62	27,56	32,28	36,22	48,03
E	in	17,72	19,69	19,69	19,69	21,65
Capacity	yd ³	0,66	0,79	0,86	0,92	1,38
Oil Flow	gal/min	23 / 26	34 / 36	34 / 36	44 / 47	65 / 79
Pressure	psi	3,857	4,286	4,286	4,286	4,286
Weight	lbs	3,711	6,044	6,822	9,378	12,622
Excavator Weight	1000 lbs	26 / 35	35 / 53	42 / 53	53 / 88	77 / 122



Quality and dependability: two features you can count on with every TRAMAC product.

All TRAMAC products are engineered for superior performance, manufactured to the most exacting specifications, and—within the guidelines of the industry's most rigid quality control program—thoroughly inspected at every stage of production. All working parts are precision-machined to the closest tolerances, and all materials meet or exceed the highest industry standards. These are but a few of the many vital reasons major contractors worldwide choose our products.

They know that with TRAMAC, reliability is crucial; a basic component conscientiously built into every unit that bears our name.