## **Hydraulic Demolition Shears** TRAVAC **HP Series**

## For carriers from 2 to 14 tons





### **HP Series Primary Demolition Shears**

- 3 models for excavators with operating weight from 2 to 14 tons
- Pressure intensifier HP BOOSTER
- Compact-designed 360° rotation
- Fully-protected cylinder
- **High power levels**
- Lower fuel consumption
- Optimal use of the carrying machine
- Interchangeable blades
- Synchronic jaw-moving system
- Fast working cycles
- Optimal power weight





# **Hydraulic Demolition Shears - HP Series**

# **Specifications and Dimensions**



MODEL		HP02	HP04	HP07
Α	in	44,37	50,79	59,45
В	in	29,33	35,83	42,32
D	in	13,78	19,09	21,65
Steel blade lenght	in	3,35	3,35	5,91
F3	t	33	38	55
Rotation	0	360	360	360
Rotation Flow	gal/min	1/2	1/2	1/2
Rotation Pressure	psi	1714	1714	1714
Open/Close Flow	gal/min	13	18	18
Op/CI Pressure	psi	2857	2857	2857
Weight	lbs	667	978	1644
Excavator Weight	1000 lbs	4 / 11	8 / 17	15 / 28
09	in	0,59	0,59	0,79

TRAMAC reserves the right to change or discontinue models and/or specifications without prior notice.

#### Quality and dependability: two features you can count on with every TRAMAC product.

All TRAMAC products are engineered for superior performance, manufactured to the most exacting specifications, and—within the guidelines of the industry's most rigid quality control program— thoroughly inspected at every stage of production. All working parts are precision—machined to the closest tolerances, and all materials meet or exceed the highest industry standards. These are but a few of the many vital reasons major contractors worldwide choose our products.

They know that with TRAMAC, reliability is crucial; a basic component conscientiously built into every unit that bears our name.



