

Multi-Utility Demolition Shears

MT Series

For carriers from 3 to 77,5 tons



Multi-Utility Demolition Shears MT Series

This attachment stands out for its operating versatility. The main structure can be fitted with different types of jaws, depending on the specific work to do.

Thanks to the interchangeability of the jaws, that can be easily and quickly replaced, the MT demolition shear is perfect to be used for any type of demolition, and especially on construction sites where is necessary to do different types of works that otherwise require the use of multiple single tools and equipment.



Multi-Utility Demolition Shears - MT Series



Multi-Utility Demolition Shears - MT Series

Specifications and Dimensions



Model		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
Rotation	°	360	360	360	360	360	360	360	360	360
Rotation Flow	gal/min	1 / 2	1 / 2	1 / 2	5 / 7	5 / 7	5 / 7	10 / 13	10 / 13	10 / 13
Rotation Pressure	psi	1714	1714	1714	1714	1714	1714	1714	1714	1714
Open/Close Flow	gal/min	7 / 13	18 / 29	23 / 36	39 / 52	44 / 55	65 / 79	79 / 92	92 / 118	105 / 131
Open/Close Pressure	psi	3142/5000	5000	5000	5000	5000	5000	5000	5000	5000
Weight	lbs	582	1133	1767	2556	3289	3856	5333	7856	8747
Carrier Weight	1000 lbs	6 / 13	11 / 24	22 / 33	33 / 48	46 / 62	55 / 77	73 / 111	97 / 133	111 / 155

"D" INTERCHANGEABLE TEETH & BLADES KIT



« D » JAWS	MT + D		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	In	46,22	54,53	62,76	74,29	81,69	88,98	99,25	107,20	114,25
	B	In	14,72	21,46	26,38	29,69	33,94	44,49	49,13	51,57	60,91
	C	in	12,01	15,16	17,52	22,95	24,53	27,91	32,44	33,50	37,17
	Blade Lenght	In	3,31	5,91	5,91	5,91	7,87	7,87	11,81	11,81	11,81
	F3	t	27,5	55,1	77,2	88,2	110,2	143,3	154,3	170,9	187,4
	Weight Total	lbs	822	1433	2278	3344	4436	5662	7369	10458	12260
	Weight	lbs	240	300	511	784	1151	1584	2036	2602	3513
		In	0,59	0,79	0,98	1,18	1,38	1,57	1,77	1,97	1,97
« S » JAWS	MT + S		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	In	45,59	53,15	60,79	73,19	82,72	87,36	97,20	107,87	115,63
	B	In	6,85	9,02	11,69	13,54	16,26	22,68	24,06	26,10	29,25
	C	In	10,04	11,50	12,68	18,94	21,89	21,26	24,76	28,50	30,87
	F3	t	32	68,3	93,7	104,7	126,8	165,3	181,9	198,4	231,5
	Weight Total	lbs	833	1427	2280	3442	4644	5613	7444	10809	12898
	Weight	lbs	251	293	513	882	1360	1536	2111	2953	4151
		In	1,18	1,18	1,38	1,57	1,97	2,36	2,56	2,76	3,15
		In	/	0,20	0,31	0,39	0,47	0,59	0,79	0,98	1,18
	In	/	4,72	5,51	7,09	10,63	12,99	14,17	17,72	19,69	
	In	/	2,76	3,94	5,51	7,87	9,45	10,24	11,81	12,60	
« P » JAWS	MT + P		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	In	/	53,07	61,93	72,87	80,08	88,66	98,78	104,69	113,23
	B	In	/	17,20	21,42	23,78	26,14	35,87	41,02	41,89	44,21
	C	In	/	13,03	15,59	20,16	20,63	24,92	30,43	28,78	31,38
	Blade Lenght	In	/	3,31	3,31	5,91	5,91	5,91	5,91	7,87	7,87
	F3	t	/	59,5	81,6	97	122,4	154,3	159,8	181,9	223,8
	Weight Total	lbs	/	1460	2349	3540	4602	5984	7896	11262	13149
	Weight	lbs	/	327	582	980	1318	1907	2562	3407	4402
		In	/	0,79	0,98	1,18	1,38	1,57	1,77	1,97	1,97