

Multi-Utility Demolition Shears

MT Series

For carriers from 3 to 70 tons



Multi-Utility Demolition Shears MT Series

This attachment stands out for its operating versatility. The main structure can be fitted with different types of jaws, depending on the specific work to do.

Thanks to the interchangeability of the jaws, that can be easily and quickly replaced, the MT demolition shear is perfect to be used for any type of demolition, and especially on construction sites where is necessary to do different types of works that otherwise require the use of multiple single tools and equipment.



Multi-Utility Demolition Shears - MT Series



Multi-Utility Demolition Shears - MT Series

Specifications and Dimensions



Model		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
Rotation	°	360	360	360	360	360	360	360	360	360
Rotation Flow	l/min	5 / 8	5 / 8	5 / 8	20 / 30	20 / 30	20 / 30	40 / 50	40 / 50	40 / 50
Rotation Pressure	bar	120	120	120	120	120	120	120	120	120
Open/Close Flow	l/min	30 / 50	70 / 110	90 / 140	150 / 200	170 / 210	250 / 300	300 / 350	350 / 450	400 / 500
Open/Close Pressure	bar	220	220/350	350	350	350	350	350	350	350
Weight	kg	262	510	795	1150	1480	1735	2400	3535	3936
Carrier Weight	t	3 / 6	5 / 11	10 / 15	15 / 22	21 / 28	25 / 35	33 / 50	44 / 60	50 / 70

"D" INTERCHANGEABLE TEETH & BLADES KIT



« D » JAWS	MT + D		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	mm	1174	1385	1594	1887	2075	2260	2521	2716	2902
	B	mm	374	545	670	754	862	1130	1248	1308	1547
	C	mm	305	385	445	583	623	709	824	845	944
	Blade Length	mm	84	150	150	150	200	200	300	300	300
	F3	t	25	50	70	80	100	130	140	155	170
	Weight Total	kg	370	645	1025	1505	1996	2548	3316	4718	5517
	Weight	kg	108	135	230	353	518	713	916	1183	1581
		mm	15	20	25	30	35	40	45	50	50
« S » JAWS	MT + S		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	mm	1158	1350	1544	1859	2101	2219	2469	2740	2937
	B	mm	174	229	297	344	413	576	611	663	743
	C	mm	255	292	322	481	556	540	629	724	784
	F3	t	29	62	85	95	115	150	165	180	210
	Weight Total	kg	375	642	1026	1549	2090	2526	3350	4864	5804
	Weight	kg	113	132	231	397	612	691	950	1329	1868
		mm	30	30	35	40	50	60	65	70	80
		mm	/	5	8	10	12	15	20	25	30
		mm	/	120	140	180	270	330	360	450	500
		mm	/	70	100	140	200	240	260	300	320
« P » JAWS	MT + P		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	mm	/	1348	1573	1851	2034	2252	2509	2659	2876
	B	mm	/	437	544	604	664	911	1042	1064	1123
	C	mm	/	331	396	512	524	633	773	731	797
	Blade Length	mm	/	84	84	150	150	150	150	200	200
	F3	t	/	54	74	88	111	140	145	165	203
	Weight Total	kg	/	657	1057	1593	2071	2693	3553	5068	5917
	Weight	kg	/	147	262	441	593	858	1153	1533	1981
		mm	/	20	25	30	35	40	45	50	50
« T » JAWS	MT + T		MT03	MT05	MT10	MT15	MT20	MT25	MT35	MT45	MT55
	A	mm	\	\	\	1851	2008	2133	2316	2547	2778
	B	mm	\	\	\	300	325	420	454	482	511
	C	mm	\	\	\	364	364	394	394	441	486
	Weight Total	kg	\	\	\	1562	1905	2418	3011	4788	5222
	Weight	kg	\	\	\	626	701	950	1083	1253	2033
		mm	\	\	\	10	15	20	25	30	35

Canada: 3421 Industriel Blvd / Laval, QC / H7L 4S3 / 1-888-663-8122 / 450-663-8122 / FAX 450-663-6797
 1711 Rte de l'Aéroport #4 / L'Ancienne Lorette, Qc / G2G 2P4 / 418-877-5557 / FAX 450-877-1886
 1-28 Steve Fonyo Dr. / Kingston, On / K7M 8N9 / 613-542-1500 / FAX 613-542-1505
 USA: 12 Orben Drive, Suite #3 / Landing, NJ 07850 / 973-770-4457 / FAX 973-770-0812
 e-mail: tramac@tramac.com <http://www.tramac.com>

